

## NEOSUN™ Ultra M8 144

NEOSUN™ Ultra M8 is the top performance reference solar module series. Based on the advanced mono M8 wafer and PERC Half-cut technology, Ultra offers as much power as 550W with outstanding cell efficiency up to 23.4% and **21.5% module efficiency**.

Thanks to the Half-Cut technology, the cell internal resistance is reduced, which provides an additional module power even while shading, cloudy weather, and in low light conditions.

23.4%

### EXCELLENT CELLS EFFICIENCY

Advanced 9BB solar cells with PERC technology provide efficiency up to 23.2% (up to 21.2% module efficiency)



Weak Sunlight

### EXCELLENT WEAK LIGHT PERFORMANCE

Solar modules from NEOSUN Energy have excellent weak light performance (morning, evening and cloudy days)

+3%

### POSITIVE POWER TOLERANCE

Guarantee from 0 to +3% as power tolerance, you can obtain more power than conventional output



### SAND AND SALT PROTECTION

Reliable quality leads to a better sustainability even in harsh environment like desert or coastline

25


### YEARS POWER WARRANTY

Even after 25 years our solar panel keeps at least 80% of its initial power output – because it's NEOSUN



### HIGH WIND AND SNOW RESISTANCE

NEOSUN Energy modules withstand snow load of up to 550 kg/m<sup>2</sup> and wind speed of up to 162km/h




For a period of twenty-five (25) years commencing on the Warranty Start Date, loss of power output of the nominal power output measured at Standard Test Conditions (STC) for the Product(s) shall not exceed:

1. For Polycrystalline Products: 2% in the first year, thereafter 0.67% per year ending with 82% in the 25th year after the Warranty Start Date.
2. For Monocrystalline Products: 3% in the first year, thereafter 0.67% per year, ending with 81% in the 25th year after the Warranty Start Date.

The Warranty Start Date shall be defined as the date of the Bill of Lading date

### I-V curves

I-V Curves of PV module NEOSUN 540W at different light power




### Electrical characteristics

Solar cells:	Mono M8 PERC 144 cells 9BB, 6x24 pcs		
Max Power	540W	545W	550W
Power Tolerance	+5W		
Voltage at Pmax (Vmp)	42.0V	42.2V	42.4V
Current at Pmax (Imp)	12.86A	12.92A	12.28A
Open-Circuit Voltage (Voc)	49.8V	50.0V	50.2V
Short-Circuit Current (Isc)	13.70A	13.76A	13.82A
Module Efficiency	21.13%	21.32%	21.52%
Max-System Voltage (VDC)	1500V(IEC), 1500V(UL)		
No. of Bypass Diodes (pcs.)	3		
Max Series Fuse (A)	25A		
Temperature Coefficient of Pmax	-0.35% / °C		
Temperature Coefficient of Voc	-0.27% / °C		
Temperature Coefficient of Isc	0.05% / °C		
Nominal Operating Cell t°C	45 ± 2°C		

\*STC Conditions (1000W/m2; 1.5 AM and 25°C Cell temperature)

### Dimensions



### Mechanical Characteristics

Cable type, Diameter and Length	Ø =4mm <sup>2</sup> , L=300±5mm
Type of Connector	Compatible type MC4
Dimension AxBxC	2256x1133x35mm
Weight	28.5 kg
Front Glass	Tempered with AR coating
Junction Box (protection degree)	IP68 Rated
Frame	Clear anodized aluminum alloy

### Qualification Test Parameters

Dielectric Insulation Voltage	6000VDC max
Operating Temperature	-40°C to +85°C
Max load	5400Pa
Hailstone impact	25mm at 23m/s
Fire safety class	Class C

### Packaging Configuration

Container	40'HQ
Pieces per pallet	30
Pallets per container	20
Pieces per container	600

**Caution: read safety and installation instructions before using this product**