

NEOSUN™ Ultra M6 120

NEOSUN™ Ultra M6 is the top performance reference solar module series. Based on the advanced mono wafer and PERC Half-cut technology, Ultra offers as much power as 460W with outstanding cell efficiency up to 23.2% and 20.3% module efficiency.

Thanks to the Half-Cut technology, the cell internal resistance is reduced, which provides an additional module power even while shading, cloudy weather, and in low light conditions.

23.2%

EXCELLENT CELLS EFFICIENCY

Advanced 9BB solar cells with PERC technology provide efficiency up to 23.2% (up to 20.3% module efficiency)



Weak Sunlight

EXCELLENT WEAK LIGHT PERFORMANCE

Solar modules from NEOSUN Energy have excellent weak light performance (morning, evening and cloudy days)

+3%

POSITIVE POWER TOLERANCE

Guarantee from 0 to +3% as power tolerance, you can obtain more power than conventional output



SAND AND SALT PROTECTION

Reliable quality leads to a better sustainability even in harsh environment like desert or coastline

25


YEARS POWER WARRANTY

Even after 25 years our solar panel keeps at least 80% of its initial power output – because it's NEOSUN



HIGH WIND AND SNOW RESISTANCE

NEOSUN Energy modules withstand snow load of up to 550 kg/m² and wind speed of up to 162km/h



For a period of twenty-five (25) years commencing on the Warranty Start Date, loss of power output of the nominal power output measured at Standard Test Conditions (STC) for the Product(s) shall not exceed:


1. For Polycrystalline Products: 2% in the first year, thereafter 0.67% per year ending with 82% in the 25th year after the Warranty Start Date.

2. For Monocrystalline Products: 3% in the first year, thereafter 0.67% per year, ending with 81% in the 25th year after the Warranty Start Date.

The Warranty Start Date shall be defined as the date of the Bill of Lading date

I-V curves

I-V Curves of PV module NEOSUN 370W at different light power




Electrical characteristics

Solar cells:	Mono M6 Half-cut PERC cells 9BB, 6x20 pcs		
Max Power	365W	370W	375W
Power Tolerance	+5W		
Voltage at Pmax (Vmp)	34.2V	34.4V	34.6V
Current at Pmax (Imp)	10.67A	10.76A	10.84A
Open-Circuit Voltage (Voc)	41.1V	41.3V	41.5V
Short-Circuit Current (Isc)	11.16A	11.26A	11.34A
Module Efficiency	19.73%	20.00%	20.27%
Max-System Voltage (VDC)	1500V(IEC), 1500V(UL)		
No. of Bypass Diodes (pcs.)	3		
Max Series Fuse (A)	20A		
Temperature Coefficient of Pmax	-0.36% / °C		
Temperature Coefficient of Voc	-0.29% / °C		
Temperature Coefficient of Isc	0.05% / °C		
Nominal Operating Cell t°C	45 ± 2°C		

*STC Conditions (1000W/m²; 1.5 AM and 25°C Cell temperature)

Dimensions



Mechanical Characteristics

Cable type, Diameter and Length	Ø =4mm ² , L=300±5mm
Type of Connector	Compatible type MC4
Dimension AxBxC	1765x1048x30mm
Weight	20.5 kg
Front Glass	Tempered with AR coating
Junction Box (protection degree)	IP68 Rated
Frame	Clear anodized aluminum alloy

Qualification Test Parameters

Dielectric Insulation Voltage	6000VDC max
Operating Temperature	-40°C to +85°C
Max load	5400Pa
Hailstone impact	25mm at 23m/s
Fire safety class	Class C

Packaging Configuration

Container	40'HQ
Pieces per pallet	35
Pallets per container	24
Pieces per container	840

Caution: read safety and installation instructions before using this product